

LIFTING BARRIERS RH-EU-M AND IND

9 M MAX.

The second model in our range is the Rh-EU-M barrier. This barrier is available in stainless steel (EU) and galvanised steel (IND) versions. These barriers are very reliable and of the highest quality, at an attractive price. Our barriers feature a solid push-rod mechanism, guaranteeing secure movement of the arm and sturdy, maintenance-free construction.

Our barriers are fitted with a door-opening sensor, shutting off the power automatically for inspection or maintenance.

TECHNICAL SPECIFICATIONS

Dimensions	686 x 608 x 1180 mm (W x D x H)
Weight	450 kg
Opening time	Approx. 10 seconds
Voltage	230/400 Volt, 50 Hz, 3 phases + 0 + earth
Power (motor)	0.75 kW
Bearings	Fully enclosed, maximum guarantee
Motor	Worm gearbox with motor
Colour	RAL 7032 (standard), other colours on request at additional cost



BARRIER INCLUDES:

- ✓ Earthing block
- ✓ Junction box IP66
- ✓ Power – circuit breaker (5 connections)
- ✓ Contact-free position switches Pilz SIL 2
- ✓ Manual operation (only possible with power switched off)

ARM

- ✓ Aluminium Ø 136 mm to Ø 100 mm
- ✓ In accordance with client's national standards
- ✓ With reflecting tape on both sides, in accordance with national standards
- ✓ Lighting not included as standard due to variations in national standards per country; possible on request

